



**Octopus Products Limited**  
 23 Gurney Crescent  
 Toronto, Ontario M6B 1S9  
 Tel 416 531-5051 Fax 416 531-3254  
 Toll Free: 1-877-OCTOLAM  
 www.octopusproducts.com

**MATERIAL SAFETY DATA SHEET**

**Section 1: PRODUCT AND COMPANY IDENTIFICATION**

Tel 416 531-5051 Fax 416 531-3254  
 Toll Free: 1-877-OCTOLAM  
 www.octopusproducts.com

**Manufacturer:**

VARIOUS

**Company Phone Number:**

**Manufacturer's emergency Phone Number**  
**(CHEMTREC):**(800) 424-9300 (U.S.),  
 (202) 482-7616 (International)

**Issue Date:** February 5, 2008

PRODUCTS: OCTOLAM

**Section 2: HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

No known hazards for material as supplied. During fabrication operations such as sawing, sanding, drilling, routing, cutting etc. dust consisting of cured resin, paper fiber and minute amounts of formaldehyde are generated at the point of operation. Formaldehyde may be released in minute but detectable amounts when material is shipped or stored in bulk quantities.

**Appearance/Odor:** Thin to thick, rigid laminate sheets, various thicknesses/colors. No significant odor.

**WARNING:**

Sanding, sawing, drilling, routing, etc. of this material may generate airborne nuisance dust. This dust may cause eye, nose, skin, and upper respiratory tract irritation. Use of appropriate personal protection and/or engineering controls (such as local exhaust ventilation) should be employed whenever sanding, sawing, drilling, routing, etc. of this material.

- Potential Health effects:** Dust generated during fabrication of this material may cause irritation of the eyes, nose skin and upper respiratory tract. Asthmatic conditions maybe aggravated by the dust generated.
- Likely Routes of Exposure:** Eye contact, skin contact and inhalation
- Eyes:** Dust generated during installation or fabricating could cause eye irritation (tears, blurred vision and redness). In case of eye contact with dusts, rinse affected eye for at least 15 minutes with clean water. If irritation persists, seek medical attention.
- Skin:** The dust generated during installation or fabrication may cause moderate skin irritation. Avoid prolonged skin exposure to dust. Rinse skin with mild soap if contact occurs. If irritation persists, seek medical attention.
- Ingestion:** Not likely to occur and not expected to cause a significant toxic response. However, ingestion of dust could cause irritation of the mouth, throat and stomach. If this occurs, rinse mouth with clean water. If irritation persists, seek medical attention.
- Inhalation:** Sanding, sawing, drilling, routing or cutting of this material may generate airborne dust that may cause eye, nose and upper respiratory tract irritation. Use appropriate personal protection and/or engineering controls (such as local exhaust ventilation whenever sanding, routing, sawing, drilling, cutting, etc. on this material.
- Medical Conditions Aggravated by Exposure:** Dust may cause skin irritation to people with pre-existing skin conditions. Asthmatic conditions may be aggravated by additional dust exposure.
- Target Organs:** Lungs (From dust generated during fabrication only)

---

**Section 3: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS**

This product does not contain regulated levels of NTP, IARC, or OSHA listed carcinogens

<u>Component</u>	<u>CAS #</u>	<u>% by Wt.</u>
Paper/Fiber	NA	40-70
Resins	NA	30-50

---

**Section 4: FIRST AID AND MEASURES**

Eye contact	If dust gets into the eyes, immediately rinse affected eye for at least 15 minutes with clean water. If irritation persists, seek medical attention.
Skin contact	If excess dust gets onto the skin, remove contaminated clothing and wash before reuse. Wash skin with soap and water. Seek medical attention if irritation occurs.
Ingestion	If dust gets into mouth, rinse mouth with clean water. Seek medical attention if necessary.
Inhalation	If excess dust is inhaled, move to fresh air. Seek medical attention if symptoms such as wheezing and/or shortness of breath occur.

---

**Section 5: FIRE FIGHTING MEASURES**

This material is a Class A combustible material. Use water spray, carbon dioxide or dry chemical foam to extinguish flames. Use water to keep cool and prevent rekindling of material.

Unusual Fire or Explosion Hazards: Sanding, sawing, drilling, routing, cutting, etc. of this material may generate a Class ST-1 dust. Safety precautions and proper ventilation as recommended by NFPA-68 for Class ST-1 dusts should be followed to prevent this or any Class ST-1 dust from presenting a explosion hazard.

Suitable Extinguishing Media: CO2, water, foam.

Possible Products of Combustion: Various oxides of carbon and nitrogen, ammonia and formaldehyde.

Protection of Firefighters: Combustion products may be irritating to eyes, skin and the respiratory tract. Firefighters should wear self-contained breathing apparatus and full fire-fighting turnout gear.

---

**Section 6: ACCIDENTAL RELEASE MEASURES**

Personal Precautions: Material is non-hazardous as supplied. Review personal protection measures in Section 8.

Methods for Clean-up: Recover undamaged materials for reuse or reclamation. Sweep or pick up scrap material and place in disposal containers.

---

**Section 7: HANDLING AND STORAGE**

Handling: Prevent dust from entering eyes. Do not breathe dust. Avoid prolong skin contact with dust and/or filings. Cut, drill, saw, sand and finish, etc. in well-ventilated areas.

Storage: Keep away from strong chemicals, solvents and excessive heat. Prolonged or extreme heat can cause damage to the surface.

---

**Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

Exposure Guidelines:	OSHA PEL 15mg/m <sup>3</sup> Total Dust 5mg/m <sup>3</sup> Respirable Dust	ACGIH TLV 10mg/m <sup>3</sup> Inhalable 3 mg/m <sup>3</sup> Respirable
Engineering Controls:	Provide adequate ventilation to maintain exposure levels below applicable limits. The use of local exhaust ventilation is recommended during fabrication work. Dust generated is a Class ST-1 dust and precautions recommended by NFPA-68 should be followed.	
Eye/face Protection:	Wear safety glasses when sawing, sanding, drilling or routing.	
Skin Protection:	Wear appropriate gloves when installing, transporting, sawing, cutting, drilling, routing or handling uninstalled pieces.	
Foot Protection:	No special protection required.	
Respiratory Protection:	Where airborne concentrations of dust are expected to exceed the allowable exposures, a NIOSH-approved respirator should be worn, chosen based on the form and concentration of the contaminant. Respirator usage must be in accordance with the OSHA Respiratory Protection Standard, 29 CFR 1910.134.	
General Hygiene Considerations:	Wash thoroughly after sawing, cutting, drilling, or routing. Have eyewash facilities immediately available.	

Additional information is available in ASTM E1132-99a

---

**Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

Color:	Various
Odor:	None
Physical State:	Solid sheet product
PH:	Not applicable
Freezing Point:	Not applicable
Boiling Point:	Not applicable
Flash Point:	Not applicable
Evaporation Rate:	Not applicable
Flammability:	Not applicable
Upper Flammability Limit:	Not applicable
Lower Flammability Limit:	Not applicable
Vapor Pressure:	Not applicable
Vapor Density:	Not applicable
Specific Gravity:	1.45
Solubility (water):	Not applicable
Auto-ignition Temperature:	Not applicable
Percent volatile, wt %:	Zero
Volatile Organic Compound (VOC) content, wt. %:	Zero. Product as supplied is fully cured and chemically inert, VOC release is extremely low.

---

**Section 10: STABILITY AND REACTIVITY**

Stability: Stable

Conditions to Avoid: Avoid exposing to oxidizers, strong chemicals, alkaline solutions and solvents.  
 Incompatible Materials: Avoid strong acids and alkaline solutions which will damage the surface appearance of the material. If spills occur, remove immediately from the material.

**Section 10: STABILITY AND REACTIVITY(continued)**

---

Hazardous Decomposition Products: Thermal decomposition product may include various oxides of carbon and nitrogen may be released.  
Hazardous Polymerization: Will not occur.

---

**Section 11: TOXICOLOGY INFORMATION**

**ACUTE EFFECTS**

Oral LD50: Not known  
Dermal LD50: Not known  
Inhalation: See Section 2  
Eye Irritation: See Section 2  
Skin irritation: See Section 2  
Sensitization: No data for product.

**CHRONIC EFFECTS**

Carcinogenicity: This product may contain trace amounts of formaldehyde which is listed by IARC as carcinogenic. The ACGIH lists formaldehyde as a suspect human carcinogen. NTP lists formaldehyde as carcinogenic. WARNING-Substance contained in this product known to the State of California to cause cancer, birth defects or other reproductive harm – formaldehyde.

Mutagenicity: No data for product.  
Reproductive Effects: No data for product.  
Developmental Effects: No data for product.

---

**Section 12: ECOLOGICAL INFORMATION**

Ecotoxicity: No data for product  
Persistence/Degradability: No data for product  
Bioaccumulation/Accumulation: No data for product  
Mobility in Environment: No data for product

---

**Section 13: DISPOSAL CONSIDERATIONS**

Disposal: Material is non-hazardous and no special treatment is required for disposal. Disposal in landfill must be in accordance with federal, state and local regulations.

---

**Section 14: TRANSPORTATION INFORMATION**

DOT: Not Regulated

---

**Section 15: REGULATORY INFORMATION**

WARNING-Substance contained in this product known to the State of California to cause cancer, birth defects or other reproductive harm - Formaldehyde.

---

**Section 16: OTHER INFORMATION**

NFPA Labeling  
Health – 1                      Fire – 0                      Reactivity – 0  
0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard

**Section 16: OTHER INFORMATION(continued)**

Acronyms:

ACGIH = American Conference of Governmental Industrial Hygienists  
ASTM = American Society for Testing and Materials  
DOT = Department of Transportation  
DOT = Department of Transportation  
IARC = International Agency for Research on Cancer  
NFPA = National Fire Protection Agency  
NIOSH = National Institute of Occupational Safety and Health  
NTP = National Toxicology Program  
OSHA = Occupational Safety and Health Administration  
PEL = Permissible Exposure Limit

**Section 16: OTHER INFORMATION(Continued)**

TLV = Threshold Limit Value  
TSCA = Toxic Substance Control Act  
TWA = Time Weighted Average  
Mg/m<sup>3</sup> = Milligrams per Cubic Meter of Air

Prepared by: Formica Corporation, John Foged, REM

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for his own particular use.

---